



ProGanics™ Biotic Soil Media



**GREEN DESIGN
ENGINEERING™**
EARTH-FRIENDLY SOLUTIONS
FOR SUSTAINABLE RESULTS™

Solutions for your Environment™

Description

ProGanics™ Biotic Soil Media™ (BSM™) is designed as an alternative to topsoil to accelerate development of depleted soils/substrates with low organic matter, low nutrient levels and limited biological activity. This Engineered Soil Media™ (ESM™) helps unleash soils to their fullest potential for vegetative establishment and more effective erosion control. ProGanics is non-toxic with bark and wood fibers that have been phytosanitized to eliminate potential weed seeds and pathogens - prior to the introduction of soil building components.

Recommended Applications

- Development of Soils with Low Organic Matter (< 5%)
- Rapid Establishment and Sustained Growth of Vegetation
- Replacement of Costly or Difficult to Obtain Topsoil
- Replacement of Compost, Peat, Manure and Other Sources of Organic Material
- Typically Installed Beneath Hydraulically-applied and Rolled Erosion Control Products (HECPs and RECPs) as Growing Media.

Soil Building and Revegetation

Mix seed and specified Prescriptive Agronomic Formulations at recommended rates in approved hydraulic seeding/mulching equipment when water has reached approximately 1/3 of the working capacity. Add ProGanics™ Biotic Soil Media at a rate of 100 pounds per 100 gallons of water (45 kg / 379 L) on hydraulic equipment with gear or positive displacement pumps and 75 pounds per 100 gallons of water (34 kg / 379 L) on centrifugal pumps while agitating; add fertilizer when the tank is approximately 3/4 full. Apply over properly prepared surfaces that are deemed geotechnically stable. Confirm specific material loading rates with equipment manufacturer.

Erosion Control Solution

Apply ProGanics as directed above being sure to include all Prescriptive Agronomic Formulations, fertilizer and seed at their recommended rates. Apply Flexterra® HP-FGM™, ProMatrix™ EFM™, or RECP over ProGanics as directed by manufacturer's recommendation. Follow all manufacturer's product selection guidelines or go to www.ProfilePS3.com for assistance.

Technical Data

Physical Properties*	Test Method	Units	Tested Value
Organic Material	ASTM D586	%	≥ 94
Mass/Unit Area	ASTM D6566 ¹	g/m ² (oz/yd ²)	≥ 392 (11.6)
Ground Cover	ASTM D6567 ¹	%	≥ 99
Water Holding Capacity	ASTM D7367	%	≥ 900
pH	ASTM D1293	n/a	6.0 ± 0.3
C:N Ratio	ASTM E1508 & EPA Method 1687	n/a	50:1 ± 10
Material Color	Observed	n/a	Brown
Performance Properties*	Test Method	Units	Tested Value
Cover Factor ²	Large Scale ^{4,5}	n/a	≤ 0.01
Percent Effectiveness ³	Large Scale ^{4,5}	%	≥ 99
Vegetation Establishment	ASTM D7322 ¹	%	≥ 850
Environmental Properties*	Test Method	Units	Tested Value
Ecotoxicity	EPA 2021.0	%	48-hr LC ₅₀ > 100%
EPA 503 Metal Pass/Fail ⁶	EPA 503 Metal Limits	Pass/Fail	Pass
Pathogen Reduction	40 CFR 503 Class A Compost	Pass/Fail	Pass
Product Composition			Typical Value
Thermally Processed Bark and Wood Fibers ⁷ (within a pressurized vessel)			89%
Proprietary blend of Polysaccharide Polymers, Biochar, Seaweed Extract, Humic Acid, Endomycorrhizae, and Beneficial Bacteria			11%
Moisture Content			12%
Properties	Test Method	Units	Nominal Value
Bag Weight	Scale	kg (lb)	22.7 (50)
Bags per Pallet	Observed	#	40

UV and weather-resistant plastic bags. Pallets are weather-proof stretch wrapped with UV resistant pallet cover.

Profile Products

750 Lake Cook Road, Ste. 440
Buffalo Grove, IL 60089
800-508-8681 or +1-847-215-1144
www.profileproducts.com

To the best of our knowledge, the information contained herein is accurate. However, Profile Products cannot assume any liability whatsoever for the accuracy or completeness thereof. Final determination of the suitability of any information or material for the use contemplated, of its manner of use and whether the suggested use infringes any patents is the sole responsibility of the user.
Profile Products 2017©