



TACKING AGENT 3^o

*PERFORMANCE PRODUCTS FOR
HYDRO-SEEDING PROFESSIONALS*

- MEETS OR EXCEEDS REQUIREMENTS FOR NON-ASPHALTIC TACKING EMULSIONS
- CONTAINS POLY-ACRYLAMIDE, CO-POLYMERS AND HYDRO-COLLOID POLYMERS
- UNIVERSITY TESTED AND PROVEN TO CONTROL EROSION WITHOUT CURING

DIRECTIONS FOR USE

ONCE YOUR HYDRAULIC SEEDER IS APPROXIMATELY 1/3 FULL OF WATER ADD TACKING AGENT III, SEED, FIBER MULCH & FERTILIZER TO THE SLURRY. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.



PHYSICAL PROPERTIES

pH RANGE	7.0 +- 1
VISCOSITY (SAYBOLT)	197 CPS +- 20
SURFACE TENSION	63.9 DYNES / CM
SPECIFIC GRAVITY	.7281

APPLICATION RATE

FIBER MULCH BINDING	
4:1 TO 3:1 SLOPE	30 LBS PER ACRE
>2:1 SLOPE	60 LBS PER ACRE
STRAW MULCH BINDING	50 LBS PER ACRE

PACKAGING

8, 25 & 50 POUND BAGS - 4 EIGHT LB BAGS PER CASE. SHIPPED 60 CASES PER 48 x 48 PALLET



DISTRIBUTED BY